



RPM	MODELLO MODEL	PORTATA FLOW		PRESSIONE PRESSURE		POTENZA POWER		PESO WEIGHT	
		l/min	GPM	bar	PSI	HP	kW	Kg	
1000	PENTA-B 25/350 R-L	25	6.6	350	5100	22.4	16.5	44	R = Presa di Forza Destra R = Right PTO Shaft  L = Presa di Forza Sinistra L = Left PTO Shaft
	PENTA-B 25/400 R-L	25	6.6	400	5800	25.6	18.8	44	
	PENTA-B 30/300 R-L	30	7.9	300	4400	23.1	17.0	44	
	PENTA-B 40/250 R-L	39	10.3	250	3600	25.0	18.4	44	
	PENTA-B 40/300 R-L	40	10.6	300	4400	30.7	22.6	44	
	PENTA-B 50/200 R-L	49	12.9	200	3000	25.1	18.5	44	
1450	PENTA-C 35/350 R-L	35	9.2	350	5100	31.4	23.1	44	Sono disponibili modelli con Doppia Presa di Forza Double PTO Shaft models are available
	PENTA-C 35/400 R-L	35	9.2	400	5800	35.9	26.4	44	
	PENTA-C 43/300 R-L	43	11.4	300	4400	33.1	24.3	44	
	PENTA-C 55/250 R-L	57	15.1	250	3600	36.5	26.8	44	
	PENTA-C 58/300 R-L	58	15.3	300	4400	44.6	32.8	44	
	PENTA-C 70/200 R-L	71	18.8	200	3000	36.4	26.8	44	

### Dimensioni d'ingombro (mm) - Overall Dimensions (mm)

