

DATA SHEET HE STATIONARY 2515 (440V-60HZ)



STANDARD FEATURES:

- Hot Dip Galvanised Frame
- Udor Triplex pump with Brass Head, Ceramic Pistons and Stainless Steel Valves
- 84L Inlet Header/By-Pass Tank
- 4-Pole Nicolini DF Electric Motor (1750rpm)
- DOL Starter with Thermal protection
- 15mt of 640 bar WP rated blue HP-Hose
- Adjustable Detergent Facility
- QC-Coupling on HP-Hose
- Easy Pull Trigger Gun with Mosmatic Swivel
- Stainless Steel twin lance with adj. Pressure
- Made in Australia - 2 Year Warranty

OPTIONAL EQUIPMENT AVAILABLE:

- Surface Cleaner
- Hurricane Underbody Washer
- Turbo lance (max 100deg C)
- Flexible Lance
- Additional HP-Hose
- Foamer
- Extension Lance
- Low Water Protection

SPECIFICATIONS & TECHNICAL FEATURES:

MODEL	PRESSURE PSI/BAR	FLOW L/MIN	VOLT/HZ	KW/HP	WEIGHT KG	DIMENSIONS L x W x H
HE 2515	3650/250	15	440/60	6.3/8.7	58	180 x 63 x 45