

HYDROMAT SERVICES P/L ABN 16 074 407 631

PO BOX 3310, Loganholme Qld. 4129

14 Glasson Drive, Bethania Qld. 4205

e-mail: hydromat@hydromat.com.au

website: www.hydromat.com.au

PHONE HOTLINE 07 3216 6252

FAX HOTLINE 07 3255 6285



HYDROMAT POWERCUBE



STANDARD FEATURES:

- **KOHLER Diesel** or **Petrol** Engine
- **HONDA** Petrol Engine available
- Diesel with Spark Arrestor as standard
- Subframe on Vibration Dampeners
- Electric start & 3 Year Engine Warranty
- 2:1 reduction Gearbox drive
- Italian Made **UDOR** Triplex pump with Brass Head, Ceramic Pistons and Stainless Steel Valves
- German Easy Pull Trigger, **MOSMATIC** High Pressure Swivel & Stainless Steel Twinlance
- 20mt of 530 bar WP rated 2-wire blue HP-Hose with Bend Restrictor
- Stainless Steel air cooled vertical Boiler rated 5000 PSI Working Pressure
- **12VDC** Boiler, **not** 240VAC – Safe for Operator and Work Environment
- Thermostatic Temperature control 0-150 deg C
- All Controls in one Panel
- Battery Isolator switch
- Emergency Shutdown
- 20 l Diesel Tank
- Hot Dip Galvanised Skid Frame
- Forklift ready and Lifting eyes for easy handling
- Made in Australia – 2Year Warranty

SPECIFICATIONS & TECHNICAL FEATURES:

MODEL	PRESSURE PSI/BAR	FLOW L/MIN	TEMP DEG C	ENGINE	WEIGHT KG	DIMENSIONS L x W x H
POWERCUBE 2815P	3770/260	15	130	KOHLER 440 14HP	220	108 x 80 x 104
POWERCUBE 2815P	3770/260	15	130	HONDA GX 390	220	108 x 80 x 104
POWERCUBE 2821P	4000/280	21	100	HONDA GX 660	240	108 x 80 x 104
POWERCUBE 2515D	3650/250	15	130	KOHLER KD 440	230	108 x 80 x 104
POWERCUBE 2821D	4000/280	21	100	KOHLER KD 425/2	270	108 x 80 x 104