Diesel Engine Driven



KOHLER or Kubota diesel engine with Electric start & 3 year engine warranty
Diamond stainless steel frame
Italian made Udor pump with brass head, ceramic pistons and Stainless Steel valves
15mt of dual wire braided blue HP-Hose
Thermal protection valve
Foam filled run flat wheels

Trigger gun with swivel
Stainless Steel lance with nozzle
Made in Australia
2 Year warranty

MODEL	PRESSURE PSI/BAR	FLOW L/MIN	ENGINE	HP	WEIGHT KG	DIMENSIONS L x W x H
HD 2815	4000/280	15	Kohler 15KD 440	11	118	94 x 66 x 85
HD 2821	4000/280	21	KOHLER 25KD 425-2	19	137	94 x 66 x 85
HD 2050	3000/200	50	KOHLER OR KUBOTA	36	460	165 x 110 x 130
HD 2070	3000/200	70	KOHLER OR KUBOTA	45	460	165 x 110 x 130
HD 4025	5800/400	25	KOHLER OR KUBOTA	36	460	165 x 110 x 130
HD 4035	5800/400	35	KOHLER OR KUBOTA	45	460	165 x 110 x 130
HD 5020	7300/500	20	KOHLER OR KUBOTA	36	460	165 x 110 x 130
HD 5027	7300/500	27	KOHLER OR KUBOTA	45	460	165 x 110 x 130

Engine Driven Hot Water Machines



Petrol or Diesel engine driven
Electric start & 3 year engine warranty
Hot Dip Galvanised frame
Italian mode Udor pump with brass head,

ceramic pistons and Stainless Steel valves • 10mt of dual wire braided blue HP-Hose • Easy pull trigger with Stainless lance

Stainless Steel air cooled vertical boiler 5000 PSI rated working pressure
 Thermostat control 0-150 deg C • Made in Australia • 2 Year Warranty

MODEL	PRESSURE PSI/BAR		TEMP DEG C		BURNER	WEIGHT KG	DIMENSIONS L x W x H
HPH 2815	4000/280	15	110	HONDA IGX 390	12VDC	240	108 x 80 x 104
HPH 2821	4000/280	21	90	HONDA GX 630	12VDC	260	108 x 80 x 104
HDH 2815	4000/280	15	90	Kohler 440K	12VDC	250	108 x 80 x 104
HDH 2821	4000/280	21	90	Kohler 425KD	12VDC	300	108 x 80 x 104
HDH 2515D	3650/250	15	110	Kohler 440KD	12VDC	270	108 x 80 x 104

www.hydromat.com.au

Clean Pro Trailers

All Clean Pro Trailers come with Hydromat Quality Fixtures and Fittings as well as:-



- 30mt of 530 bar WP rated 2-wire blue HP-Hose with Bend Restrictor on Stainless Steel Hose Reel
 20mt ³/₄" Inlet Hose on Stainless Steel Hose
- 20mt 34" Inlet Hose on Stainless Steel Hose Reel on Cleanpro 600 Models
- 6001 or 10001 fully plumbed in Water Tank
- Stainless Steel air cooled vertical Boiler rated 5000 PSI Working Pressure
- 12VDC Boiler, not 240VAC Safe for Operator and Work Environment
- Thermostatic Temperature control 0-150 degC
- All Electrical Controls in one Panel
- Battery Isolator switch
- Emergency Shutdown
- High Visibility Amber Warning/Strobe light
- Hot Dip Galvanised Trailer, Alko running gear, Weatherproof & Lockable Machinery box to Protect Equipment when not in use.
- Fully Made in Australia 2 Year Warranty

	MODEL	PRESSURE PSI/BAR	-	TEMP DEG C	ENGINE	TARE KG	GVM KG	DIMENSIONS L x W x H
	600P HW	4000/280	15	130	HONDA	630	1450	365 X 178 X 155
5	600D HW	3650/250	15	130	KOHLER	620	1450	365 X 178 X 155
	1000P CW	4000/280	15	N/A	HONDA	620	1700	365 X 178 X 155
	1000D CW	3650/250	15	N/A	KOHLER	630	1700	365 X 178 X 155

ACCESSORIES

Hydromat stock & sell a range of high quality accessories to compliment our range of Industrial Cleaning Equipment. Please contact us for additional information.



Hydromat reserves the right to change the specifications or design of its equipment from time to time.





Made in Australia

HEAVY DUTY INDUSTRIAL CLEANING EQUIPMENT SINCE 1996

www.hydromat.com.au

PETROL ENGINE DRIVEN



- Genuine Honda OHV engine with low oil alert & 3 year engine warranty · Heavy duty frame with pneumatic wheels
- Italian made Udor pump with brass head, ceramic pistons and Stainless Steel valves
- Thermal protection valve
- IOmt dual wire braided blue HP-Hose
- Adjustable detergent facility
- Easy trigger gun with swivel • QC-Coupling on HP-Hose
- Made in Australia

MODEL A SERIES	PRESSURE PSI/BAR	FLOW LT/MIN	MODEL HONDA	HP	WEIGHT KG	DIMENSIONS L x W x H
HP 1712A	2500/170	12	GX 200	6.5	31	65 x 55 x 85
HP 2015A	3000/200	15	GX 390	13	60	75 x 65 x 70
HP 2019A	3000/200	19	GX 390	13	62	75 x 65 x 70
HP 2815A	4000/280	15	GX 390	13	62	75 x 65 x 70



- Genuine Honda OHV engine with low oil alert & 3 year engine warranty Diamond Stainless steel frame Italian made Udor pump with brass head, ceramic pistons and Stainless Steel valves Thermal protection valve I5mt dual wire braided blue HP-Hose Adjustable detergent facility • QC-Coupling on HP-Hose
- Foam filled run flat wheels Made in Australia • 2 Year Warranty

MODEL DIAMOND SERIES	PRESSURE PSI/BAR	FLOW LT/MIN	MODEL HONDA	HP	WEIGHT KG	DIMENSIONS L x W x H
HP 1712	2500/170	12	GX200	6.5	42	65 x 60 x 50
HP 2019	3000/200	19	GX390	13	62	80 x 60 x 59
HP 2815D	4000/280	15	GX 390	13	72	94 x 66 x 85
HP 2815R	4000/280	15	GX 390	13	72	94 x 66 x 85
HP 2020	3000/200	20	GX 390	13	79	94 x 66 x 85
HP 2821	4000/280	21	GX 630	23	98	94 x 66 x 85
HP 2530	3650/250	30	GX 660	25	98	94 x 66 x 85
HP 2038	3000/200	38	GX 660	25	101	94 x 66 x 85
HP 3521	5000/350	21	GX 660	25	101	94 x 66 x 85
HP 4019	6000/400	19	GX 690	28	103	94 x 66 x 85
HP 5016	7300/500	16	GX 690	28	135	106 x 66 x 85
HP 2050	3000/200	50	KOHLER	35	150	106 x 66 x 85
HP 4025	5800/400	25	KOHLER	35	150	106 x 66 x 85
HP 5020	7250/500	20	KOHLER	35	150	1 06 x 66 x 8 5

Notes:

COLD WATER ELECTRIC



- Diamond Stainless Steel frame
- Italian made Udor pump with brass head, ceramic pistons and Stainless Steel valves
- 4-Pole elec motor with thermal protection
- Thermal protection valve



- 10mt dual wire braided blue HP-Hose
- Adjustable detergent facility

	the second s						
	MODEL	PRESSURE		VOLT/AMP	KW/HP	WEIGHT	DIMENSIONS
2		PSI/BAR	L/MIN			KG	LXWXH
	HYDROMATE 100	1500/100	9	240/10	2.2/3	26	50 x 30 x 32
	HYDROMATE 160	2350/160	9	240/15	2.6/3.6	28	50 x 30 x 32
ļ	H/MATE 100 PRO	1500/100	9	240/10	2.2/3	36	65 x 60 x 45
	H/MATE 160 PRO	2350/160	9	240/15	2.6/3.6	38	65 x 60 x 45







潮	-	
	HE	

			100	$-\lambda_{c}$		and the second
MODEL	PRESSURE PSI/BAR	FLOW L/MIN	VOLT/AMP	KW/HP	WEIGHT KG	DIMENSIONS L x W x H
HE 1210	1750/120	10	240/15	2.6/3.5	42	80 x 40 x 55
HE 2515	3650/250	15	415/20	6.5/8.5	48	80 x 40 x 55
HE 2030	3000/200	30	415/32	11/15	72	94 x 66 x 85
HE 2821	4000/275	21	415/32	11/15	72	94 x 66 x 85
HE 2530	3650/250	30	415/32	15/20	128	90 x 60 x 65
HE 2038	3000/200	38	415/32	15/20	128	90 x 60 x 65
HE 3521	5000/350	21	415/32	15/20	128	90 x 60 x 65
HE 4019	5800/400	19	415/32	15/20	130	90 x 60 x 65
HE 5016	7300/500	16	415/32	15/20	142	90 x 60 x 65

HOT WATER ELECTRIC

- HOTBOX
- Diamond Stainless Steel frame Stainless Steel air cooled vertical boiler
- 5000 PSI rated working pressure
- Thermostat control 0-150 deg C
- 240VAC or 12VDC versions available Up to 90deg continuous hot water
- @211/min flow
- 20 I diesel tank
- Heavy duty construction
- Made in Australia 2 Year Warranty

MODEL	PRESSURE PSI/BAR		TEMP DEG C	Volt/Amp	KW/HP	WEIGHT KG	DIMENSIONS L x W x H
350/240V	5000/350	21	80-130	240/10	0.6/1	90	80 x 64 x 100
350/12VDC	5000/350	21	80-130	12/30	0.6/1	90	80 x 64 x 100



- Diamond Stainless Steel frame
- Udor triplex pump with brass head. ceramic pistons Stainless Steel valves 4-Pole twin bearing electric motor with
- flexible coupling drive
- Stainless steel air cooled vertical boiler 5000 psi working pressure
- 15mt dual wire braided blue HP-Hose Easy pull trigger with Stainless Steel lance
- Adjustable detergent facility
- Double spiral heating coil
- Thermostat control 0-150 deg C
- Made in Australia 2 Year Warranty


1	MODEL	PRESSURE PSI/BAR	FLOW L/MIN	VOLT/AMP	KW/HP	WEIGHT KG	DIMENSIONS L x W x H
L	HC 1111	1600/110	11	240/15	2.6/3.6	150	85 x 70 x 100
	HC 1210	1750/120	10	240/15A	2.6/3.6	150	85 x 70 x100
	HC 2515	3650/250	15	415/20	6.3/8.7	180	85 x 70 x 100
	HC 2821	4000/280	21	415/32	11/15	240	85 x 70 x 100

Mosmatic Surface Cleaners Pump Out Vacuum Cleaner



Hydromat Pump out vacuum cleaners are used for efficient water recovery and recycling from construction sites and applications where no drain is available. Hydromat vacuum cleaners are covered by a 2 year warranty and Australia wide spare parts back up.

Mosmatic Surface Cleaners are made from stainless steel, ranging in size from 200mm to 750mm diameter with or without recovery ports. Please contact us to discuss which model is right for you.



- - Diamond Stainless Steel frame
 - Udor triplex pump with brass head, ceramic pistons and Stainless Steel valves
 - Thermal protection valve
 - 4-Pole double flange Nicolini elec motor
 - DOL starter with thermal protection
 - I5mt dual wire braided blue HP-Hose
 - Stainless Steel twin lance with adj pressure

 Adjustable detergent facility QC-Coupling on HP-Hose Trigger gun with swivel Made in Australia • 2 Year Warranty

HE IS IN THE IS INTERNED. INTO IS INTERNED AS INTERNED. INTO IS INTERNED. INTO ISTURATE ISTURATE. INTO ISTURATE ISTURATE. INTO ISTURATE ISTURATE. INTO ISTURATE ISTURATE ISTURATE. INTO ISTURATE ISTURATE ISTURATE. INTO ISTURATE ISTURATE.										
PRESSURE PSI/BAR	FLOW L/MIN	VOLT/AMP	KW/HP	WEIGHT KG	DIMENSIONS L x W x H					
750/120	10	240/15	2.6/3.5	42	80 x 40 x 55					
3650/250	15	415/20	6.5/8.5	48	80 x 40 x 55					
3000/200	30	415/32	11/15	72	94 x 66 x 85					
4000/275	21	415/32	11/15	72	94 x 66 x 85					
3650/250	30	415/32	15/20	128	90 x 60 x 65					
3000/200	38	415/32	15/20	128	90 x 60 x 65					

 Trigger gun with swivel Stainless Steel lance with adj fan Made in Australia • 2 Year Warranty