

HYDROMAT SERVICES P/L ABN 16 074 407 631

PO BOX 3310, Loganholme Qld. 4129
2/71 Richland Ave. Coopers Plains Qld. 4108
e-mail: hydromat@hydromat.com.au
website: www.hydromat.com.au
PHONE HOTLINE 07 3216 6252
FAX HOTLINE 07 3255 6285



DATA SHEET HOTCUBE MODELS



STANDARD FEATURES:

- Hot Dip Galvanised Frame
- Udor Triplex pump with Brass Head, Ceramic Pistons and Stainless Steel Valves
- 4-Pole twin Bearing Electric Motor with flexible Coupling Drive
- 10mt of 640 bar WP rated blue HP-Hose
- Easy Pull Trigger with Stainless lance
- Adjustable Detergent Facility
- Stainless Steel air cooled vertical Boiler rated 5000 PSI Working Pressure
- Thermostat control 0-150 deg C
- 20 l Diesel Tank
- Made in Australia - 2 Year Warranty
- Planned Maintenance available

OPTIONAL EQUIPMENT AVAILABLE:

- Steam Nozzle
- Steam Facility
- Timed Total Stop
- Cover Panels
- Turbo lance (max 100deg C)
- Wet Sandblaster
- Flexible Lance
- Additional HP-Hose

SPECIFICATIONS & TECHNICAL FEATURES:

MODEL	PRESSURE PSI/BAR	FLOW L/MIN	TEMP DEG C	VOLT/A	KW/HP	WEIGHT KG	DIMENSIONS L x W x H
HC 1111	1600/110	11	110	240/15	2.6/3.6	150	85 x 70 x 100
HC 1410	2050/140	9	120	240/15	2.6/3.6	150	85 x 70 x 100
HC 2515	3650/250	15	90	415/20	6.3/8.7	180	85 x 70 x 100
HC 2821	4000/280	21	80	415/32	11/15	240	85 x 70 x 100